## An Advanced Simulator of Vertical Cavity Surface Emitting Lasers (VCSEL)



Copyright 2006 Crosslight Software Inc. www.crosslight.com


#### **Contents**

- Self-consistent models in PICS3D/VCSEL module.
- Basic VCSEL modeling capabilities.
- Advanced features.
- Conclusions.



#### **Crosslight VCSEL Models**

PICS3D/VCSEL modules include quantum mechanical, electrical, thermal and microcavity optical effects, with stronger interaction than for any other optoelectronic devices.




Software Inc.

#### **Contents**

- Self-consistent models in PICS3D/VCSEL module.
- Basic VCSEL modeling capabilities.
- Advanced features.
- Conclusions.



#### Schematic of Conventional VCSEL Model





- 2D-slice and cylindrical coordinates are used to define 3D structure of VCSEL.
- Thickness of spacer layer is adjusted so that the center of MQW and standing wave coincide.

CRO<u>S</u>L

Software Inc.

### Current Spreading Effect






 Difference in L-I is mainly due to current spreading effect.



## Longitudinal Modes in VCSEL




Schematic of surface emitting lasers of front and back emission.


Schematic of a simple multi-layer optical model for DFB/DBR gratings.


- Material layers form SEL DBR/DFB gratings.
- Compared with edge DFB/DBR LD, VCSEL has fewer number of grating layers: ~50.
- More accurate to use multi-layer optics to describe the longitudinal modes.
- Transfer matrix method is used to calculate optical transmission between layers.



#### Computation of Lateral Optical Modes of VCSEL by Using EIM








- A convenient traditional fiber-like EIM implemented.
- Optionally sophisticated EIM mode solver may be activated for accuracy.
- EIM is especially useful, when a VCSEL has an oxide confinement aperture.


G. R. Hadley et. Al., "*Comprehensive numerical modeling of vertical-cavity surface-emitting lasers*", IEEE J. Quantum Electron., Vol. 32, pp607-616, 1996.



## Self-heating effect in VCSEL simulation



Thermal VCSEL simulation: temperature distribution



L-I characteristic: Iso- vs. Non-isothermal simulation

- Large substrate with bottom contact attached to external heat sink@300K.
- Self-heating effect causes degradation of slope efficiency.




#### **Contents**

- Self-consistent models in PICS3D/VCSEL module.
- Basic VCSEL modeling capabilities.
- Advanced features.
- Conclusions.




#### Automatic VCSEL Cavity Design Module



- Tune\_vcsel utility can adjust VCSEL structure so that emission wavelength tunes with material gain peak.
- Also, position of MQW is automatically adjusted so that the center of standing wave and MQW coincide.






- Incident light at shorter wavelength (well above bandgap wavelength) is absorbed and generates carriers.
- Photo-carriers causes population inversion and lasing action at near the bandgap energy.


Software Inc.

#### Multi-lateral Modes Calculation of VCSEL



L-I curve from multimode calculation.

- VCSEL has similar lateral mode competition behavior as edge lasers.
- Perfect rotation symmetry assumed here for VCSEL structure.






#### Resonating Wavelength of multimode VCSEL using EIM


Using effective index method(EIM), the resonating wavelength of oxideconfined VCSELs with different apperture diameters have been calculated and compared with others. The benchmark structure is taken from

IEEE J. Quan. Elec., vol. 37, p1618, 2001.






#### Spectrum of multi-lateral mode of VCSEL



Different lateral modes produce different propagation constants which causes multiple peaks in simulated emission spectrum as a result of the self-consistent calculation.




#### Non-symmetric VCSEL in Cylindrical Coordinate




Half-slice of non-symmetric VCSEL.

Model required:

- Full 3D drift-diffusion model.
- Lateral mode with both radian and angular dependence.
- Full 3D interaction of electrical and optical behaviors.
- Typical application: VCSEL with top or side contact in a non-symmetric position.




## **Rectangular Shape VCSEL**




- In this example, only a half of the device is simulated to save computational cost.
- Full 3D current flow model is used.



#### Multimode transient (large signal) simulation



# Vertical external cavity surface emitting laser (VECSEL)



CROSLIGHT Software Inc.

#### **Conclusions**

- A rather comprehensive set of selfconsistent physical models for VCSEL simulation implemented in PICS3D.
- Utilities such as round-trip gain calculator and VCSEL structure tuner makes it convenient for initial set-up.
- The final simulation run integrates all the important model elements for a VCSEL.

